



D-115)))


2-WAY full-range
Loudspeaker



Front



Side



Top

D-SERIES

SPECIFICATIONS

Frequency Response	55 Hz - 18 kHz (+3 dB)
Sensitivity	99 dB SPL (1W @ 1m)
Nominal Impedance	8 ohms
Power Handling	450 watts (rms) , 900 watts (program) 1600 watts (peak)
Maximum SPL	126dB
Nominal Dispersion	80° horizontal , 50° vertical
Crossover Frequency	2.5 kHz
Enclosure Construction	18 mm birch plywood with structured
Finish	Wear-resistant textured black paint
Grille	Powder coated perforated steel, foam backed
Options	1 x Integral pole mount socket
Input Connectors	Speakon NL4 x 2
Dimensions (H x W x D)	710mm x 450 mm x 495 mm
Net Weight	33 kg

DRIVERS

Low Frequency:

1 x 15(in) 380 mm dia , 75 mm(2.9in)voice coil dia

High Frequency:

1 x 2(in) 44 mm voice coil dia , 23 mm(1in)throat dia

FEATURES

- 2-way full range loudspeaker
- Low distortion
- 80° x50° dispersion
- Built-in HF protection device

APPLICATIONS

- Auditorium conference room, multi function hall, Discotheque club and small performance event

DESCRIPTIONS

D-115 consists of one 15" LF loudspeaker and one 2" compress driver, built-in optimized frequency division network and HF protection device

FREQUENCY RESPONSE

