





H-15ND


2-WAY full-range
Loudspeaker




Front



Side



Top



Bottom

H-SERIES

SPECIFICATIONS

| | |
|------------------------|---------------------------------------------|
| Frequency Response | 55 Hz - 17 kHz (± 3 dB) |
| Sensitivity | 99 dB SPL (1W @ 1m) |
| Nominal Impedance | 8 ohms |
| Power Handling | 550 watts (rms) , 2200 watts (peak) |
| Maximum SPL | 126 dB |
| Nominal Dispersion | 90° horizontal, 60° vertical |
| Crossover Frequency | 1.6 kHz |
| Enclosure Construction | 18 mm birch plywood with structured |
| Finish | Wear-resistant textured black paint |
| Grille | Powder coated perforated steel, foam backed |
| Suspension Hardware | 3 x 4-Position fly track |
| Options | 1 x Integral pole mount socket |
| Input Connectors | Speakon NL4 x 2 |
| Dimensions (H x W x D) | 710 mm x 450 mm x 435 mm |
| Net Weight | 26.8 kg |

DRIVERS

Low Frequency (neodymium magnet) :

1 x 15 (inch) 380 mm dia , 100 mm (4 inch) voice coil dia

High Frequency (neodymium magnet):

1 x 2.8 (inch) 72 mm voice coil dia , 38 mm (1.5 inch) throat dia

FEATURES

- 2-way full range loudspeaker
- with monitor function
- multi-angle cabinet structure
- Phase-converted LF radiation

APPLICATIONS

- auditorium, karaoke room, discotheque, club and kinds of performance.

DESCRIPTIONS

H15ND consists of one 15" LF speaker and one 2.8" compress driver, the speaker is made of high magnetic flux Neodymium as magnetic circuit system, effectively improve output sensitivity, and meanwhile decrease its weight. Multi-angle cabinet design, can also be used as stage monitor loudspeaker. Three flying tracks with four position points on the top and back, two flying points on the two sides are convenient for the different installation. There is support pole on its bottom, can connect with H-18SP, H-18B in a string. Phase-converted LF radiation. Built-in high-quality crossover, and can also choose Bi-Amp frequency division mode.

FREQUENCY RESPONSE

