

H-SERIES


SPECIFICATIONS

Frequency Response	65 Hz - 18 kHz (± 3 dB)
Sensitivity	96 dB SPL (1W @ 1m)
Nominal Impedance	4 ohms
Power Handling	200 watts (rms) , 800 watts (peak)
Maximum SPL	119 dB
Nominal Dispersion	100° horizontal, 100° vertical
Crossover Frequency	2.2 kHz
Enclosure Construction	18 mm birch plywood with structured
Finish	Wear-resistant textured black paint)
Grille	Powder coated perforated steel, foam backed
Suspension Hardware	2 x 4-Position fly track ,
Options	1 x Integral pole mount socket
Input Connectors	Speakon NL4 x 2
Dimensions (H x W x D)	350 mm x 454 mm x 320 mm
Net Weight	13.2 kg




H-8ND

2-WAY full-range
Loudspeaker



Front



Side



Top



Bottom

DRIVERS

Low Frequency(neodymium magnet):

2 x 8(inch) 210 mm dia , 44 mm(1.73inch)voice coil dia

High Frequency:

1 x 1(inch) 25 mm voice coil dia

FEATURES

- 2-way full range loudspeaker
- with monitor function
- Included-angle cabinet structure
- Phase-converted LF radiation

APPLICATIONS

- conference room, KTVroom, small bar and club

DESCRIPTIONS

H8ND consists of two 8"LF speaker and two 1"high-frequency driver, the LF speaker is made of high magnetic flux Neodymium as magnetic circuit system, effectively improve output sensitivity , and meanwhile decrease its weight. Included-angle cabinet design increase the horizontal dispersion, two flying tracks with four position points on the top, three flying points on the back and two sides are convenient for the different installation. Phase-converted LF radiation

FREQUENCY RESPONSE

